


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRCFP
- **Nitta Japan code:**



Construction: 2 plies top cotton, bottom polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	Cotton fabric	PU	Impregnated fabric	
Thickness:	-		-	mm (approx.)
Colour:	-	White	-	
Hardness:	-		-	
Profile:	-		-	

Total thickness:	1,4	mm (approx.)
Weight:	1,3	kg/m² (approx.)
Max. width:	2000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	6	N/mm
Advised pretension:	2 - 3	N/mm
Maximum allowable tension:	8	N/mm
Temperature range:	-20 to +80	°C

Minimum pulley diameters:		
Flexing:	15	mm
Backflexing:	15	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- Dough handling in bakeries
- Panner belt
- Excellent release of dough in bakeries
- Retractory conveyors
- Oil and grease resistant

Date of issue 15-05-2014-1