

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 R 71
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	PVC	
Thickness:	0,7		0,5	mm (approx.)
Colour:	White	White	White	
Hardness:	65 Shore A		90 Shore A	
Profile:	-		SQPR	

Total thickness: 3,2 **mm (approx.)**
Weight: 3,6 **kg/m² (approx.)**
Max. width: 3000 **mm**
Belt support: Sliderbed (Rollers), Flat

Rating at 1% elongation: 10 **N/mm**
Advised pretension: 4 - 7 **N/mm**
Maximum allowable tension: 20 **N/mm**
Temperature range: -10 **to** +90 **°C**

Minimum pulley diameters:
Flexing: 50 **mm**
Backflexing: 75 **mm**

Special approval: FDA, 10/2011/EC + amendments

Applications:
 Conveyor belt for the food industry
 Conveying of meat, fish and poultry products
 Conveying of fried and non-fried potato chips
 Oil and grease resistant

Date of issue 21-03-2014-2

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com